



**Quality features:**

1. Wheel cover with guide slots guard against jamming and slipping of chain.
2. Forged swivel hooks and latches prevent twisting of chain and reduce unintentional unhooking of the unit or the load.
3. Chain guide and stripper ensures proper fit of chain over pocket wheel.
4. Two-stage gear reduction with hardened gears and pinion.

Model		CB-B								
Capacity (ton)		0.25	0.5	1	1.5	2	3	5	7.5	10
Standard lifting height (m)		2.5	2.5	2.5	2.5	2.5	3	3	3	3
Running Test Load (ton)		0.3125	0.625	1.25	1.875	2.5	3.75	6.25	9.375	12.5
Headroom H (mm)		280	345	376	442	470	548	688	765	765
Load Chain Dia.(mm)	Columns	1	1	1	1	1	1	2	3	4
	Dia+Pitch	4×12	5×15	6×18	7×21	8×24	10×28	9×27	9×27	9×27
Effort to required to lifi max.load (N)		226	235	245	255	324	363	353	373	380
Dimension (mm)	A	121	148	172	196	210	255	280	433	463
	B	114	132	151	173	175	205	189	189	189
	C	24	25	30	33	35	40	42	56	56
	D	31	31.5	37.5	42.5	45	50	53	85	85
Net Weight (kg)		6.5	9.3	12.2	16.5	19.5	32	41.1	61.6	75.7
Paching Measurements (l×w×h) (mm)		23×16×15	30×17×18	32×18×19	37×20×24	37×20×24	43×40×30	47×44×35.5	62×47×39.5	53×51×46.5
Extra Weight per meter of extre lift (kg)		0.81	1	1.29	1.61	1.92	2.68	4.1	6.86H	7.73