



Capacity Kg	Lifting Height	Model	Lifting Speed	Hoist Motor	Travel Speed	Trolley Motor	Hoist Duty		Trolley Duty		H	C	Adapted beam width
	m		m/min	KW	m/min	KW	FEM	ISO	FEM	ISO	(mm)	(mm)	
2000	6,9 12,15,18	ESL020	5/0.8	3.2/0.45	20/5	0.37	3M	M6	2M	M5	210	556	150 ~ 300
3200	6,9 12,15,18	ESL032	5/0.8	3.2/0.45	20/5	0.37	3M	M5	2M	M5	210	556	150 ~ 300
5000	6,9 12,15,18	ESL050	5/0.8	6.1/1	20/5	0.37	2M	M5	2M	M5	260	596	200 ~ 350
6300	6,9 12,15,18	ESL063	5/0.8	6.1/1	20/5	0.37	1Am	M4	2M	M5	260	596	200 ~ 350
8000	6,9 12,15,18	ESL080	5/0.8	9.5/1.5	20/5	0.75	3M	M6	2M	M5	325	750	200 ~ 410
10000	6,9 12,15,18	ESL100	5/0.8	9.5/1.5	20/5	0.75	2M	M5	2M	M5	325	750	200 ~ 410
12500	6,9 12,15,18	ESL125	4/0.6	12.5/2	20/5	0.75	1Am	M4	2M	M5	325	750	200 ~ 410
16000	6,9 12,15,18	ESL160	4/0.6	16/2.6	20/5	0.75*2	2M	M5	2M	M5	400	920	300 ~ 450
20000	6,9 12,15,18	ESL200	4/0.6	16/2.6	20/5	0.75*2	1Am	M4	2M	M5	400	920	350 ~ 450
8000	20,24,28,32,36	ESL080H	8/1.3	12.5/2	20/5	0.75	2M	M5	2M	M5	325	750	200 ~ 410
10000	20,24,28,32,36	ESL080H	8/1.3	16/2.6	20/5	0.75	2M	M5	2M	M5	325	750	200 ~ 410
12500	20,24,28,32,36	ESL125H	6.3/1	16/2.6	20/5	0.75*2	1Am	M4	2M	M5	325	750	200 ~ 410